

GRUNDOWINCH®



3-Ton Variable Speed **GRUNDOWINCH**



Specs

- 11'L x 5'W x 4'H
- 3,280 feet of 10mm (3/8 inch) Cable
- Line speed: 160 lf/min @ 1.5 ton, 80 lf/min at 3 ton

The 3-Ton Variable Speed Grundowinch is compact, making it ideal for getting in and out of easements, right-of-ways and residential areas. The downhole boom offers ease of set up in manholes and job site excavations. And the unit's infinite speed adjustment capability makes the 3-ton Grundowinch ideal for a wide range of pulling applications!

Ideal For:

Lining Contractors

- Ultra Violet Cured Liners
- Small Diameter Sliplining
- "Pull in Place" Cured in Place Liners

Large Diameter Pipe Cleaning and CCTV Contractors

- High Pressure Hoses for Pipe Cleaning
- Assist with Large CCTV Camera Crawlers

Cable Pulling Utility Contractors

- Electric Power Cables, Fiber Conduits, Telecommunication Conduits



TT Technologies

2020 E New York Street • Aurora, IL 60502 • 800-533-2078 • 630-851-8200 • FAX 630-851-8299

www.tttechnologies.com • E-mail info@tttechnologies.com

Copyright© 2011, TT Technologies, Inc.
GRUNDOWINCH is a registered
trademark of TT Technologies, Inc.
Specifications subject to change at any time.